




<b>Category</b>	Commercial Linear
<b>Application</b>	Commercial, Education
<b>Specification</b>	Performance

# Proline Evo

Proline EVO 1800mm CCT

**Code:** APRE6/1



## PRODUCT FEATURES

- Surface linear suitable for educational and commercial applications
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Corridor Function for dimmable microwave sensor options
- Modern contemporary fully enclosed high performance surface luminaire
- Low glare and uniform light distribution
- Self-test emergency option
- Powered by Philips and Tridonic drivers

### GENERAL INFORMATION

<b>Wattage</b>	30W - 53W
<b>Lumens Delivered</b>	4300lm - 7400lm (4000K)
<b>Lm/W</b>	130lm/W
<b>Beam Angle</b>	120
<b>CRI</b>	80
<b>CCT</b>	3000/4000K
<b>Input</b>	220-240V
<b>Operating Temp</b>	-10°C - 40°C
<b>SDCM</b>	6
<b>UGR</b>	25
<b>Product Weight without Packaging</b>	4.7 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP20
<b>IK Rating</b>	IK06
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Lumen Depreciation</b>	L70 54,000h
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Height</b>	73 mm



Category	Commercial Linear
Application	Commercial, Education
Specification	Performance

# Proline Evo

Proline EVO 1800mm CCT

Code: APRE6/1

