





Prism Pro Mini Fire Rated

Prism Pro Mini

Code: APRILEDP/MINI/CCT

| | |
|---------------|---|
| Category | Downlights |
| Application | Ancillary, Hospitality, Residential, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- Ultra slim remote driver with loop-in, loop-out push fit terminals provide an easy and efficient installation
- Can be used as the sole light source or as a complimentary product to Prism Pro / Prism Pro Anti-Glare
- Detachable LED driver for fast fix install
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Ultra slim remote driver with loop-in, loop-out push fit terminals provide an easy and efficient installation
- Unique angled LED driver for easy installation through the smaller downlight cut out
- Low profile design and arched remote driver allows installation into shallow ceiling voids
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

GENERAL INFORMATION

| | |
|----------------------------------|----------------------|
| Wattage | 5W |
| Lumens Delivered | 450lm (4000K) |
| Lm/W | 90lm/W (4000K) |
| Beam Angle | 60 |
| CRI | 80 |
| CCT | 2700/3000/4000/6000K |
| Input | 220-240V |
| Operating Temp | -5°C - 25°C |
| SDCM | 6 |
| UGR | 29 |
| Cut-Out Size | 42mm |
| Product Weight without Packaging | 0.144 kg |

TECHNICAL INFORMATION

| | |
|--------------------------------|--|
| Light Source | LED |
| Colour / Finish | White |
| Fire Rated | Yes |
| IP Rating | IP65 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 7 |
| CE Mark | Yes |
| Diameter | 55 mm |
| Height | 50 mm |
| Accessories | APRILEDP/MINIBZ/BLK, APRILEDP/MINIBZ/CH, APRILEDP/MINIBZ/SC, ACFLP/3 |

