



Category	Downlights	
Application	Ancillary, Hospitality, Residential, Retail	
Specification	Architectural	

OCTO Prism Pro Fire Rated Connected by WiZ

OCTO Prism Pro Fire Rated Downlight Connected by WiZ RGBTW Code: APRIP/1/OCTOW/RGBTW







PRODUCT FEATURES

- IP65 Dimmable LED WiZ enabled tunable white Fire Rated Downlight suitable for residential and commercial applications
- Tunable between 2700K 6500K via WiZ app and voice control offering a choice of 2 outputs, in one luminaire
- Remote driver with 2x1.5mm₄ + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations

GENER	RAL INFORMATION
Wattage	8W
Lumens Delivered	500lm - 550lm (2700K - 6500K)
Lm/W	68lm/w - 75lm/w (2700K - 6500K)
Beam Angle	65
CRI	80
CCT	2700-6500K
Input	220-240V
Operating Temp	-20°C - 35°C
SDCM	6
UGR	25
Cut-Out Size	73mm
Product Weight without Packaging	0.305 kg

- Connects directly to your WiFi network using Bluetooth technology to support seamless
 pairing
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- · Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
Fire Rated	Yes		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	7		
CE Mark	Yes		
Diameter	90 mm		
Height	58 mm		

ansell_lightingAnsell Lighting







Category	Downlights	
Application	Ancillary, Hospitality, Residential, Retail	
Specification	Architectural	

OCTO Prism Pro Fire Rated OCTO Prism Pro Fire Rated Downlight Connected by WiZ RGBTW

Code: APRIP/1/OCTOW/RGBTW











