Prism Pro

Part of the Downlights product category

Model	Prism Pro CCT Fire Rated Downlight Dual Wattage
Code	APRIP/1
Application	Ancillary, Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	5W - 7W
Operating Temp	-20°C - 35°C
Lumens Delivered	560lm - 740lm
lm/W	110lm/W - 105lm/W
CCT	2700/3000/4000/6000K
UGR	25
Beam Angle	65

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.285 kg
Colour / Finish	White
Diameter	90 mm
Height	62 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.85
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm¸ + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Low profile design and remote driver allows installation into shallow ceiling voids

ACCESSORIES

APRILEDPBZ/BLK	Prism Pro Matt Black Bezel
APRILEDPBZ/SC	Prism Pro Satin Chrome Bezel
APRILEDPBZ/CH	Prism Pro Chrome Bezel
ACFLP/3	LED Emergency Lighting Pack Maintained / Non-Maintained





Prism Pro

Part of the Downlights product category

Model	Prism Pro CCT Fire Rated Downlight Dual Wattage
Code	APRIP/1
Application	Ancillary, Hospitality, Residential, Retail













