



# Prism Pro

Part of the Downlights product category



**Model** Prism Pro CCT Fire Rated Downlight Dual Wattage  
**Code** APRIP/1  
**Application** Ancillary, Hospitality, Residential, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	5W - 7W
<b>Operating Temp</b>	-20°C - 35°C
<b>Lumens Delivered</b>	560lm - 740lm
<b>lm/W</b>	110lm/W - 105lm/W
<b>CCT</b>	2700/3000/4000/6000K
<b>UGR</b>	25
<b>Beam Angle</b>	65

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	0.285 kg
<b>Colour / Finish</b>	White
<b>Diameter</b>	90 mm
<b>Height</b>	62 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	6
<b>CRI</b>	80
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Recessed
<b>Power Factor</b>	0.85
<b>L70 @ 25°C</b>	L70 B50 60,000h

## PRODUCT FEATURES

- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm<sub>2</sub> + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Low profile design and remote driver allows installation into shallow ceiling voids

## ACCESSORIES

APRILEDPBZ/BLK	Prism Pro Matt Black Bezel
APRILEDPBZ/SC	Prism Pro Satin Chrome Bezel
APRILEDPBZ/CH	Prism Pro Chrome Bezel
ACFLP/3	LED Emergency Lighting Pack Maintained / Non-Maintained





# Prism Pro



Part of the Downlights product category

**Model** Prism Pro CCT Fire Rated Downlight Dual Wattage  
**Code** APRIP/1  
**Application** Ancillary, Hospitality, Residential, Retail

