





OCTO Prism Pro Anti-Glare FRD Connected by WiZ

OCTO Prism Pro Anti-Glare FRD Connected by WiZ

Code: APRIPAG/1/OCTOW/TW

Category	Downlights
Application	Ancillary, Hospitality, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing Anti-Glare Downlight suitable for residential and commercial applications
- Supplied with matt white bezel as standard.
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Low profile design and remote driver allow installation into shallow ceiling voids
- Tunable between 2700K - 6500K via WiZ app and voice control
- Anti-glare design to create visual comfort
- Remote driver with 2x1.5mm + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

GENERAL INFORMATION

Wattage	8W
Lumens Delivered	350lm - 410lm (2700K - 6500K)
Lm/W	55lm/W
Beam Angle	55
CRI	80
CCT	2700-6500K
Input	220-240V
Operating Temp	-20°C - 35°C
SDCM	6
UGR	19
Cut-Out Size	73mm
Product Weight without Packaging	0.285 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
Fire Rated	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 60,000h
Warranty (Years)	7
CE Mark	Yes
Diameter	88 mm
Height	80 mm

