# Prism Pro

Part of the Downlights product category

| | |
|---|---|
| **Model** | Prism Pro CCT Fire Rated Gimbal Dual Wattage Satin Chrome |
| **Code** | APRIPG/1/SC |
| **Application** | Ancillary, Hospitality, Residential, Retail |

## GENERAL INFORMATION

| | |
|---|---|
| **Input** | 220-240V |
| **Wattage** | 5W - 7W |
| **Operating Temp** | -20°C - 35°C |
| **Lumens Delivered** | 530lm - 690lm (4000K) |
| **lm/W** | 100lm/W (4000K) |
| **CCT** | 2700/3000/4000/6000K |
| **UGR** | 28 |
| **Beam Angle** | 70 |

## MATERIAL INFORMATION

| | |
|---|---|
| **Main Material** | Aluminium |
| **Diffuser Material** | Polycarbonate |
| **Product Weight without Packaging** | 0.285 kg |
| **Colour / Finish** | Satin Chrome |
| **Diameter** | 86 mm |
| **Height** | 67 mm |

## TECHNICAL INFORMATION

| | |
|---|---|
| **Class Protection** | 1 |
| **Light Source** | LED |
| **SDCM (Initial Macadam)** | 6 |
| **CRI** | 80 |
| **Internal / External** | Internal |
| **Surface / Recessed / Suspended** | Recessed |
| **Power Factor** | 0.85 |
| **L70 @ 25°C** | L70 B50 60,000h |

## PRODUCT FEATURES

- 220-240V IP20 dimmable LED 4 CCT selectable fire rated performance gimbal suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- 30° tilt angle
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation







# Prism Pro

Part of the Downlights product category

| | |
|---|---|
| **Model** | Prism Pro CCT Fire Rated Gimbal Dual Wattage Satin Chrome |
| **Code** | APRIPG/1/SC |
| **Application** | Ancillary, Hospitality, Residential, Retail |















