



# Prism Pro

Part of the Downlights product category



**Model** Prism Pro CCT Fire Rated Gimbal Dual Wattage White  
**Code** APRIPG/1/WH  
**Application** Ancillary, Hospitality, Residential, Retail

## GENERAL INFORMATION

Input	220-240V
Wattage	5W - 7W
Operating Temp	-20°C - 35°C
Lumens Delivered	530lm - 690lm (4000K)
lm/W	100lm/W (4000K)
CCT	2700/3000/4000/6000K
UGR	28
Beam Angle	70

## MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without	0.285 kg
Packaging	
Colour / Finish	White
Diameter	86 mm
Height	67 mm

## TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.85
L70 @ 25°C	L70 B50 60,000h

## PRODUCT FEATURES

- 220-240V IP20 dimmable LED 4 CCT selectable fire rated performance gimbal suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- 30° tilt angle
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm, + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation





# Prism Pro



Part of the Downlights product category

**Model** Prism Pro CCT Fire Rated Gimbal Dual Wattage White

**Code** APRIPG/1/WH

**Application** Ancillary, Hospitality, Residential, Retail

