





Emergency

Performance






Hospitality, Industrial, Retail




Raven

Raven Emergency Downlight Non-Maintained Code: ARALED/ER/3NM/ST







Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- Recessed Self-test emergency downlight with self-contained inverter and battery pack
- Option of escape route or open area models
- Pre-wired with 150mm rubber insulated cable for ease of installation
- Integral components for fast-fit installation

Category

Application

Specification

- High performance optic design
- Up to 15 metres spacing between luminaires

GENERAL INFORMATION		
Wattage	3W	
Lumens Delivered	110lm (Emergency)	
Beam Angle	30/140	
CRI	70	
CCT	6500K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	6	
Cut-Out Size	95mm	
Product Weight without Packaging	0.28 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 50,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	110 mm	
Height	97 mm	