



Raven



Part of the Emergency product category

Model Raven Emergency Downlight Non-Maintained Open Area White
Code ARALED/OA/3NM/ST
Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	130lm (Emergency)
CCT	6500K
Beam Angle	45

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without	0.28 kg
Packaging	
Colour / Finish	White
Diameter	110 mm
Height	97 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.3
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Recessed Self-test emergency downlight with self-contained inverter and battery pack
- Integral components for fast-fit installation
- Option of escape route or open area models
- High performance optic design
- Pre-wired with 150mm rubber insulated cable for ease of installation





Raven



Part of the Emergency product category

- Model** Raven Emergency Downlight Non-Maintained Open Area White
- Code** ARALED/OA/3NM/ST
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

