





Wall Lights

Architectural







Reef Adjustable

Reef CCT Adjustable Surface Downlight White Code: AREELEDA








Category

Application

Specification



Hospitality, Outdoor, Residential, Retail

PRODUCT FEATURES

- Durable indoor/outdoor surface mounted downlight suitable for residential and hospitality applications
- Polycarbonate construction ideal for coastal applications
- Unique lockable installation base plate with push fit loop-in loop-out terminals for ease of installation
- Choice of matt white or black finishes
- CCT selectable between 3000K, 4000K and 6000K
- Non-dimmable

| GENERAL INFORMATION | | |
|----------------------------------|-----------------|--|
| Wattage | 5W | |
| Lumens Delivered | 480lm (4000K) | |
| Lm/W | 97lm/W (4000K) | |
| Beam Angle | 90 | |
| CRI | 80 | |
| CCT | 3000/4000/6000K | |
| Input | 220-240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 6 | |
| Product Weight without Packaging | 0.215 kg | |
| | | |

www.ansell-lighting.com

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP54 | |
| Class Protection | 2 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling | |
| Lumen Depreciation | L80 54,000h | |
| Warranty (Years) | 3 | |
| CE Mark | Yes | |
| Diameter | 85 mm | |
| Height | 110 mm | |