



Reef



Part of the Wall Lights product category

Model	Reef L Bi-Directional Wall Light Black
Code	AREFL/BD/B/1
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	54W
Operating Temp	-25°C - 40°C
Lumens Delivered	6000lm (4000K)
lm/W	110lm/W (4000K)
CCT	3000K/4000K
Beam Angle	85

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.87 kg
Colour / Finish	Black
Diameter	151 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.9
L70 @ 25°C	L70 198,000h

PRODUCT FEATURES

- Durable outdoor wall light suitable for commercial and hospitality applications
- Polycarbonate construction ideal for coastal applications
- Supplied with 2x interchangeable Gobo inserts, allowing for a variety of decorative beam angle light effects
- CCT selectable between 3000K and 4000K
- Unique lockable installation base plate with push fit loop-in loop-out terminals for ease of installation

ACCESSORIES

AREFL/CWL/B/1	Reef L Cowl Black
---------------	-------------------





Reef



Part of the Wall Lights product category

Model	Reef L Bi-Directional Wall Light Black
Code	AREFL/BD/B/1
Application	Commercial, Education, Healthcare, Hospitality, Outdoor, Retail

