



Reef



Part of the Wall Lights product category

Model	Reef S Bi-Directional Wall Light Black
Code	AREFS/BD/B/1
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	10W
Operating Temp	-20°C to 40°C
Lumens Delivered	700lm
lm/W	70lm/W
CCT	3000/4000K
UGR	21
Beam Angle	70

MATERIAL INFORMATION

Main Material	Nylon
Product Weight without	0.325 kg
Packaging	
Colour / Finish	Black
Height	170 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	External
Surface / Recessed / Suspended	Wall
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Durable outdoor wall light suitable for residential and hospitality applications
- Polycarbonate construction ideal for coastal applications
- Supplied with 2x interchangeable Gobo inserts, allowing for a variety of decorative beam angle light effects
- CCT selectable between 3000K and 4000K
- Unique lockable installation base plate with push fit loop-in loop-out terminals for ease of installation





Reef



Part of the Wall Lights product category

Model Reef S Bi-Directional Wall Light Black

Code AREFS/BD/B/1

Application Hospitality, Outdoor, Residential, Retail

