Signal Pro

Part of the Emergency product category

7YR | Li-Pro 7YR | IP20 | IK06

Model	Signal PRO High Output Non-Maintained Emergency Downlight White
Code	ASIP/1/HO/W
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.5W
Operating Temp	0°C-45°C
Lumens Delivered	250lm
CCT	5000K
Beam Angle	Open area - 140° Escape route - 160°x40°

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	PMMA
Product Weight without Packaging	0.24 kg
Colour / Finish	White
Diameter	50 mm
Height	31 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal
Surface / Recessed / Suspended	Recessed


PRODUCT FEATURES

- Ultra-low profile recessed emergency downlight
- High specification optic design and performance allows increased spacing providing reduced cost
- LiFePO4 Lithium battery provides enhanced product lifetime
- Supplied with open area and escape route interchangeable lenses
- Available both in Self-Test and DALI emergency variant

ACCESSORIES

ASIP/1/WB/W	Signal PRO Wide Bezel Kit White





Signal Pro

7YR | Li-Pro 7YR | IP20 | IK06

Part of the Emergency product category

Model	Signal PRO High Output Non-Maintained Emergency Downlight White
Code	ASIP/1/HO/W
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

