Sleek

5YR IP65 IK08 ON-SITE WARRANTY 2 YEARS

Part of the Bulkheads product category

Model	Sleek Bulkhead 2CCT Multi Wattage
Code	ASLE/1
Application	Commercial, Industrial, Outdoor

GENERAL INFORMATION

Input	220-240V
Wattage	5W - 8W
Operating Temp	-10°C - 40°C
Lumens Delivered	570lm - 960lm (4000K)
lm/W	114lm/W - 119lm/W (4000K)
CCT	3000/4000K
Beam Angle	120

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.4 kg
Colour / Finish	Black
Height	76 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- All polycarbonate multi-purpose bulkhead suitable for external commercial applications
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- CCT selectable between 3000K and 4000K
- Instant light output and unlimited switching
- Non-dimmable





Sleek

Part of the Bulkheads product category

Model	Sleek Bulkhead 2CCT Multi Wattage
Code	ASLE/1
Application	Commercial, Industrial, Outdoor



