



Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance

## Signal Pro

Signal Pro Emergency Downlight Non-Maintained Code: ASPRLED/LI/3M/DA







## PRODUCT FEATURES

- LiFePO4 Lithium battery provides enhanced product lifetime
- · High specification optic design and performance allows increased spacing providing reduced cost
- 70mm to 120mm cut-out

- Supplied with open area and escape route interchangeable lenses
- DALI emergency as standard
- If not connected to DALI network Self-test mode operates automatically

	GENERAL INFORMATION
Wattage	2.5W
Lumens Delivered	240lm(OA) / 230lm(ER)
Lm/W	115lm/W
Beam Angle	Open area - 144° Escape route - 143°x120°
CRI	Ra 70
ССТ	6000K+/- 5000K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	6
Cut-Out Size	72mm
Product Weight without Packag	<b>ing</b> 0.441 kg

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333

TECHNICA	al information
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 72,000h
Warranty (Years)	7
CE Mark	Yes
Diameter	84 mm
Height	35 mm
Emergency Output Duration	3 Hr













Category	Emergency
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance

## Signal Pro

Signal Pro Emergency Downlight Non-Maintained Code: ASPRLED/LI/3M/DA





	SPARES	
ASRP/19	6 4V 1500mAh LiFePO4 Renlacement Battery	Т

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333





