Swift

Part of the Emergency product category

Model	Swift Bulkhead Maintained / Non-Maintained White
Code	ASWTLED/3M
Application	Ancillary



GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	64lm (Emergency), 173lm (Standard)
CCT	6500K
Beam Angle	105/120

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.324 kg
Colour / Finish	White
Height	100 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Supplied with self-adhesive legend
- Supplied with self-adhesive legend
- Optic design provides optimum performance for escape route lighting
- Side and rear cable entries
- Screwless gear tray for ease of installation

Swift

5YR | Ni-Cd 5YR | IP65 | IK08 | ON-SITE WARRANTY 2 YEARS

Part of the Emergency product category

Model	Swift Bulkhead Maintained / Non-Maintained White
Code	ASWTLED/3M
Application	Ancillary



