



# Swift



Part of the Emergency product category

<b>Model</b>	Swift Bulkhead Maintained / Non-Maintained White
<b>Code</b>	ASWTLED/3M
<b>Application</b>	Ancillary

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	3W
<b>Operating Temp</b>	0°C - 40°C
<b>Lumens Delivered</b>	64lm (Emergency), 173lm (Standard)
<b>CCT</b>	6500K
<b>Beam Angle</b>	105/120

## MATERIAL INFORMATION

<b>Main Material</b>	Polycarbonate
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without</b>	0.324 kg
<b>Packaging</b>	
<b>Colour / Finish</b>	White
<b>Height</b>	100 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>CRI</b>	70
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Wall
<b>L70 @ 25°C</b>	L70 B50 50,000h

## PRODUCT FEATURES

- Supplied with self-adhesive legend
- Supplied with self-adhesive legend
- Optic design provides optimum performance for escape route lighting
- Side and rear cable entries
- Screwless gear tray for ease of installation





# Swift



Part of the Emergency product category

**Model** Swift Bulkhead Maintained / Non-Maintained White  
**Code** ASWTLED/3M  
**Application** Ancillary

