



## Swift Bulkhead Maintained / Non-Maintained White



- Supplied with self-adhesive legend
- Supplied with self-adhesive legend
- Optic design provides optimum performance for escape route lighting
- Side and rear cable entries
- Screwless gear tray for ease of installation
- Viewing distance 17 metres

### Features

|           |   |
|-----------|---|
| Feature 1 | Supplied with self-adhesive legend                                  |
| Feature 2 | Supplied with self-adhesive legend                                  |
| Feature 3 | Optic design provides optimum performance for escape route lighting |
| Feature 4 | Side and rear cable entries   |
| Feature 5 | Screwless gear tray for ease of installation                        |
| Feature 6 | Viewing distance 17 metres  |

### General Information

|           |     |
|-----------|-----|
| Lamp Type | LED |
| Emergency | Yes |



|                                |                                    |
|--------------------------------|------------------------------------|
| IP Rating                      | IP65                               |
| IK Rating                      | IK08                               |
| Class Protection               | 1                                  |
| Internal / External            | Internal / External                |
| Surface / Recessed / Suspended | Ceiling, Wall                      |
| Warranty (Years)               | 3                                  |
| Material                       | Polycarbonate                      |
| Technical Information          |                                    |
| Wattage                        | 3W                                 |
| Lumens Delivered               | 64lm (Emergency), 173lm (Standard) |
| Beam Angle                     | 105/120                            |
| CRI                            | 70                                 |
| CCT                            | 6500K                              |
| Input                          | 220/240V                           |
| Hertz                          | 50/60Hz                            |
| Operating Temp                 | 0°C - 40°C                         |
| Lumen Depreciation             | L70 50,000h                        |

