



# Taurus



Part of the Bollards product category

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| <b>Model</b>       | Taurus Bollard 1000mm Self-Test Emergency                                   |
| <b>Code</b>        | ATAUB/1/SM3                                                                 |
| <b>Application</b> | Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail |

## GENERAL INFORMATION

|                         |                         |
|-------------------------|-------------------------|
| <b>Input</b>            | 220-240V                |
| <b>Wattage</b>          | 13W-27W                 |
| <b>Operating Temp</b>   | 0°C - 50°C              |
| <b>Lumens Delivered</b> | 1100lm - 2600lm (4000K) |
| <b>lm/W</b>             | 110lm/W (4000K)         |
| <b>CCT</b>              | 3000/4000K              |
| <b>Beam Angle</b>       | 140                     |

## MATERIAL INFORMATION

|                                         |            |
|-----------------------------------------|------------|
| <b>Main Material</b>                    | Aluminium  |
| <b>Product Weight without Packaging</b> | 6.25 kg    |
| <b>Colour / Finish</b>                  | Anthracite |
| <b>Diameter</b>                         | 180 mm     |
| <b>Height</b>                           | 1,000 mm   |

## TECHNICAL INFORMATION

|                                       |                |
|---------------------------------------|----------------|
| <b>Class Protection</b>               | 1              |
| <b>Light Source</b>                   | LED            |
| <b>SDCM (Initial Macadam)</b>         | 3              |
| <b>CRI</b>                            | 80             |
| <b>Internal / External</b>            | External       |
| <b>Surface / Recessed / Suspended</b> | Floor, Surface |
| <b>Power Factor</b>                   | 0.62           |
| <b>L70 @ 25°C</b>                     | L70 72,000h    |

## PRODUCT FEATURES

- Robust die-cast aluminium bollard with a textured graphite finish suitable for education, commercial and hospitality outdoor applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 3 outputs, in one luminaire
- High efficiency upto 100lm/w
- Die-cast aluminium head with polycarbonate lens
- Innovative base plate design allows greater installation flexibility





# Taurus



Part of the Bollards product category

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| <b>Model</b>       | Taurus Bollard 1000mm Self-Test Emergency                                   |
| <b>Code</b>        | ATAUB/1/SM3                                                                 |
| <b>Application</b> | Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail |

