



Taurus

Part of the Bollards product category



Model	Taurus Bollard 1000mm
Code	ATAUB/1
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	10W-24W
Operating Temp	-25°C - 50°C
Lumens Delivered	1100lm - 2600lm (4000K)
lm/W	110lm/W (4000K)
CCT	3000/4000K
Beam Angle	140

MATERIAL INFORMATION

Main Material	Aluminium
Product Weight without Packaging	6.19 kg
Colour / Finish	Anthracite
Diameter	180 mm
Height	1,000 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Floor, Surface
Power Factor	0.96
L70 @ 25°C	L70 72,000h

PRODUCT FEATURES

- Robust die-cast aluminium bollard with a textured graphite finish suitable for education, commercial and hospitality outdoor applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 3 outputs, in one luminaire
- High efficiency upto 100lm/w
- Die-cast aluminium head with polycarbonate lens
- Innovative base plate design allows greater installation flexibility





Taurus



Part of the Bollards product category

Model	Taurus Bollard 1000mm
Code	ATAUB/1
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

