



Tauro



Part of the Bollards product category

Model	Tauro Bollard Silver Grey
Code	ATAURO/1/SG
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	6W - 24W
Operating Temp	-30°C - 50°C
Lumens Delivered	750lm - 2900lm (4000K)
lm/W	125lm/W (4000K)
CCT	3000K/4000K
Beam Angle	140

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	5.13 kg
Colour / Finish	Silver
Diameter	170 mm
Height	1,040 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Floor
Power Factor	0.97
L70 @ 25°C	L70 60,000h

PRODUCT FEATURES

- Robust die-cast aluminium bollard with a textured graphite finish suitable for education, commercial and hospitality outdoor applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 4 outputs, in one luminaire
- Precision-engineered lensed optic delivers exceptional light distribution and performance, ensuring maximum efficiency and visual comfort
- Removable head design allows easy access to the integrated CCT and wattage switches, seamlessly housed within the head for quick adjustments and enhanced convenience during installation or maintenance
- Comes complete with a AFIX connector (AFIXIP/1/SC/3C) for quick and easy IP rated connection

ACCESSORIES

ATAURO/HS/SG	Tauro Bollard Half Shield Silver Grey
ARMKIT/1	Bollard Root Mounting Kit





Tauro



Part of the Bollards product category

- Model** Tauro Bollard Silver Grey
- Code** ATAURO/1/SG
- Application** Commercial, Education, Healthcare, Hospitality, Industrial, Retail

