



Telic



Part of the Floodlights product category

Model	Telic CCT Floodlight 30W Black
Code	ATEL30/1/B
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	30W
Operating Temp	-20°C - 40°C
Lumens Delivered	2900lm (4000K)
lm/W	98lm/W (4000K)
CCT	3000/4000/6000K
Beam Angle	90

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without	0.54 kg
Packaging	
Colour / Finish	Black
Height	225 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Wall
Power Factor	0.95
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Modern slimline LED floodlight with sleek unique design suitable for residential and commercial applications
- Die-cast construction and heat sink design providing optimised thermal characteristics for optimum LED life and performance
- CCT selectable between 3000K, 4000K and 6000K
- Plug and play PIR complete with manual override facility
- Loop-in, loop-out junction back on the rear of the fitting

ACCESSORIES

ATEL/PIR/B	Telic PIR Black
ATEL/1/RFPIR/B	Telic RF PIR Black





Telic



Part of the Floodlights product category



- Model** Telic CCT Floodlight 30W Black
- Code** ATEL30/1/B
- Application** Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Residential, Retail

