





Thunder ECO

Thunder ECO Multi Wattage 1500mm Daylight
Code: ATHECO5/DL

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance



PRODUCT FEATURES

- Robust, high performance LED non-corrosive suitable for ancillary areas and industrial applications
- Twist off end cap and push fit terminals aid fast and easy installation
- Non-dimmable
- Power selectable; offering high and low output option in each length
- Supplied complete with versatile stainless steel mounting clips. Clips can be located anywhere along the spine of the luminaire

GENERAL INFORMATION

Wattage	32W - 47W
Lumens Delivered	4100lm - 5800lm
Lm/W	131lm/W - 122lm/W
Beam Angle	100/140
CRI	80
CCT	6500K
Input	220/240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	27
Product Weight without Packaging	0.967 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling
Lumen Depreciation	L80 54,000h
Warranty (Years)	3
CE Mark	Yes

