












Thunder ECO

Thunder ECO Multi Wattage 1500mm Daylight Code: ATHECO5/DL







- Robust, high performance LED non-corrosive suitable for ancillary areas and industrial applications
- Twist off end cap and push fit terminals aid fast and easy installation
- Non-dimmable

- Power selectable; offering high and low output option in each length
- Supplied complete with versatile stainless steel mounting clips. Clips can be located anywhere along the spine of the luminaire

GENERAL INFORMATION		
Wattage	32W - 47W	
Lumens Delivered	4100lm - 5800lm	
Lm/W	131lm/W - 122lm/W	
Beam Angle	100/140	
CRI	80	
CCT	6500K	
Input	220-240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
UGR	27	
Product Weight without Packaging	0.967 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	3	
CE Mark	Yes	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750