












Topline EVO


Topline EVO CCT Multi Wattage 1200mm Corridor Code: ATLEVO4/CF/DM3

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Industrial, Retail
Specification	Performance









- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- High efficiency up to 140 lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Innovative spring clip gear tray release aids fast and easy installation
- Selectable CCT between 3000K, 4000K and 5700K
- Power selectable; offering high and low output option in each length
- · Instant light output with unlimited switching
- Self-test, lithium emergency option

GENERAL INFORMATION			
Wattage	31W		
Lumens Delivered	2500lm - 4300lm (4000K)		
Lm/W	140lm/W		
Beam Angle	105/140		
CRI	80		
CCT	3000/4000/5700K		
Input	220-240V		
Operating Temp	5°C - 40°C		
SDCM	3		
UGR	24		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP20		
Class Protection	1		
Internal / External	Internal		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L80 54,000h		
Warranty (Years)	5		
CE Mark	Yes		
Height	70 mm		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

