









Industrial, Retail

Performance

Battens and Weatherproofs




Topline EVO

Topline EVO CCT Multi Wattage 1500mm DALI-Code: ATLEVO5/DM3








Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- High efficiency up to 140 lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Innovative spring clip gear tray release aids fast and easy installation
- Selectable CCT between 3000K, 4000K and 5700K
- Power selectable; offering high and low output option in each length
- · Instant light output with unlimited switching
- Self-test, lithium emergency option

GENERAL INFORMATION		
Wattage	24W - 43W	
Lumens Delivered	3300lm - 6000lm (4000K)	
Lm/W	140lm/W	
Beam Angle	105/140	
CRI	80	
CCT	3000/4000/5700K	
Input	220-240V	
Operating Temp	5°C - 40°C	
SDCM	3	
UGR	25	
Product Weight without Packaging	1.824 kg	
	<u> </u>	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	70 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

