




Topline EVO

Topline EVO CCT Multi Wattage 1800mm
Code: ATLEVO6/M3

| | |
|---------------|--|
| Category | Battens and Weatherproofs |
| Application | Ancillary, Commercial, Education, Healthcare, Industrial, Retail |
| Specification | Performance |



PRODUCT FEATURES

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- High efficiency up to 140 lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Innovative spring clip gear tray release aids fast and easy installation
- Selectable CCT between 3000K, 4000K and 5700K
- Power selectable; offering high and low output option in each length
- Instant light output with unlimited switching
- Self-test, lithium emergency option

| GENERAL INFORMATION | |
|----------------------------------|-------------------------|
| Wattage | 32W - 56W |
| Lumens Delivered | 4400lm - 7800lm (4000K) |
| Lm/W | 140lm/W |
| Beam Angle | 105/140 |
| CRI | 80 |
| CCT | 3000/4000/5700K |
| Input | 220-240V |
| Operating Temp | 5°C - 40°C |
| SDCM | 6 |
| UGR | 30 |
| Product Weight without Packaging | 1.924 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|--------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP20 |
| Class Protection | 1 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Ceiling, Suspended |
| Lumen Depreciation | L80 54,000h |
| CE Mark | Yes |
| Height | 70 mm |

