



Topline Evo



Part of the Battens and Weatherproofs product category

Model Topline EVO CCT Multi Wattage 1800mm Self-Test Emergency

Code ATLEVO6/SM3

Application Ancillary, Commercial, Education, Healthcare, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	34W - 59W
Operating Temp	5°C - 40°C
Lumens Delivered	4400lm - 7800lm (4000K)
lm/W	140lm/W
CCT	3000/4000/5700K
UGR	30
Beam Angle	105/140

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.924 kg
Colour / Finish	White
Height	70 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.8
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- Selectable CCT between 3000K, 4000K and 5700K
- High efficiency up to 140 lm/W
- Power selectable; offering high and low output option in each length
- Excellent light uniformity through high transmittance polycarbonate diffuser





Topline Evo



Part of the Battens and Weatherproofs product category

Model Topline EVO CCT Multi Wattage 1800mm Self-Test Emergency
Code ATLEVO6/SM3
Application Ancillary, Commercial, Education, Healthcare, Industrial, Retail

