



# Topline Evo



Part of the Battens and Weatherproofs product category

**Model** Topline EVO CCT Multi Wattage 1800mm  
**Code** ATLEVO6  
**Application** Ancillary, Commercial, Education, Healthcare, Industrial, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	33W - 58W
<b>Operating Temp</b>	-10°C - 40°C
<b>Lumens Delivered</b>	4400lm - 7800lm (4000K)
<b>lm/W</b>	140lm/W
<b>CCT</b>	3000/4000/5700K
<b>UGR</b>	30
<b>Beam Angle</b>	105/140

## MATERIAL INFORMATION

<b>Main Material</b>	Steel
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	1.924 kg
<b>Colour / Finish</b>	White
<b>Height</b>	70 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Power Factor</b>	0.8
<b>L70 @ 25°C</b>	L70 B50 54,000h

## PRODUCT FEATURES

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- Selectable CCT between 3000K, 4000K and 5700K
- High efficiency up to 140 lm/W
- Power selectable; offering high and low output option in each length
- Excellent light uniformity through high transmittance polycarbonate diffuser





# Topline Evo



Part of the Battens and Weatherproofs product category

**Model** Topline EVO CCT Multi Wattage 1800mm  
**Code** ATLEVO6  
**Application** Ancillary, Commercial, Education, Healthcare, Industrial, Retail

