





Industrial, Retail

Performance





Battens and Weatherproofs




Topline EVO

Topline EVO CCT Multi Wattage 1800mm Code: ATLEVO6








Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

- High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications
- High efficiency up to 140 lm/W
- Excellent light uniformity through high transmittance polycarbonate diffuser
- Innovative spring clip gear tray release aids fast and easy installation
- Selectable CCT between 3000K, 4000K and 5700K
- Power selectable; offering high and low output option in each length
- · Instant light output with unlimited switching
- Self-test, lithium emergency option

| GENERAL INFORMATION | | |
|----------------------------------|-------------------------|--|
| Wattage | 33W - 58W | |
| Lumens Delivered | 4400lm - 7800lm (4000K) | |
| Lm/W | 140lm/W | |
| Beam Angle | 105/140 | |
| CRI | 80 | |
| CCT | 3000/4000/5700K | |
| Input | 220-240V | |
| Operating Temp | -10°C - 40°C | |
| SDCM | 3 | |
| UGR | 30 | |
| Product Weight without Packaging | 1.924 kg | |

| TECHNICAL INFORMATION | | |
|--------------------------------|--------------------|--|
| Light Source | LED | |
| Colour / Finish | White | |
| IP Rating | IP20 | |
| Class Protection | 1 | |
| Internal / External | Internal | |
| Surface / Recessed / Suspended | Ceiling, Suspended | |
| Lumen Depreciation | L80 54,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| Height | 70 mm | |
| | | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

