



@ansell\_lighting



ansellighting




Ansell Lighting



ansell\_lighting

## Topline 6 LED Batten OCTO Smart Control

**Code:** ATLLED4/OCTO/M3

|                                                                                   | Code      | A    | B   | C  | D  |
|-----------------------------------------------------------------------------------|-----------|------|-----|----|----|
|  | ATLLED4   | 1220 | 600 | 65 | 65 |
|                                                                                   | ATLLED5   | 1525 | 600 | 65 | 65 |
|                                                                                   | ATLLED6   | 1745 | 600 | 65 | 65 |
|                                                                                   | ATLLED2X4 | 1220 | 600 | 65 | 65 |
|                                                                                   | ATLLED2X5 | 1525 | 600 | 65 | 65 |
|                                                                                   | ATLLED2X6 | 1745 | 600 | 65 | 65 |

- High performance LED batten for multi-purpose applications
- Steel body construction with powder coat finish
- Polycarbonate end caps
- Integral switch allows the installer a choice of 3000K or 4000K colour temperatures

- Exceeds performance of T5 equivalents
- Unique opal diffuser design for optimum performance and light distribution
- Instant light output with unlimited switching
- LED lifespan L70 36,000 hours

| GENERAL INFORMATION |               |
|---------------------|---------------|
| Wattage             | 26W           |
| Lumens Delivered    | 2616lm        |
| Lm/W                | 100lm/W       |
| CRI                 | Ra 80         |
| CCT                 | 4000K         |
| Input               | 220/240V      |
| Operating Temp      | -10°C to 40°C |

| TECHNICAL INFORMATION          |                    |
|--------------------------------|--------------------|
| Light Source                   | LED                |
| IP Rating                      | IP20               |
| Class Protection               | 1                  |
| Internal / External            | Internal           |
| Surface / Recessed / Suspended | Surface, Suspended |
| Warranty (Years)               | 5                  |
| CE Mark                        | Yes                |
| Height                         | 65 mm              |

