



@ansell_lighting



ansellighting




Ansell Lighting



ansell_lighting

Topline 6 LED Batten OCTO Smart Control

Code: ATLLED5/OCTO/M3

	Code	A	B	C	D
	ATLLED4	1220	600	65	65
	ATLLED5	1525	600	65	65
	ATLLED6	1745	600	65	65
	ATLLED2X4	1220	600	65	65
	ATLLED2X5	1525	600	65	65
	ATLLED2X6	1745	600	65	65

- High performance LED batten for multi-purpose applications
- Steel body construction with powder coat finish
- Polycarbonate end caps
- Integral switch allows the installer a choice of 3000K or 4000K colour temperatures

- Exceeds performance of T5 equivalents
- Unique opal diffuser design for optimum performance and light distribution
- Instant light output with unlimited switching
- LED lifespan L70 36,000 hours

GENERAL INFORMATION	
Wattage	34W
Lumens Delivered	3656lm
Lm/W	107lm/W
CRI	Ra 80
CCT	4000K
Input	220/240V
Operating Temp	-10°C to 40°C

TECHNICAL INFORMATION	
Light Source	LED
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface, Suspended
Warranty (Years)	5
CE Mark	Yes
Height	65 mm

