




# Tornado EVO

Tornado EVO CCT Multi Wattage 600mm Switch  
Code: ATORE2/1/DD1

|               |   |
|---------------|---|
| Category      | Battens and Weatherproofs   |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail |
| Specification | Performance   |



## PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

| GENERAL INFORMATION              |                         |
|----------------------------------|-------------------------|
| Wattage                          | 9W/18W                  |
| Lumens Delivered                 | 1600lm - 3100lm (4000K) |
| Lm/W                             | 150lm/W (4000K)         |
| Beam Angle                       | 120                     |
| CRI                              | 80                      |
| CCT                              | 4000/5000/6500K         |
| Input                            | 220/240V                |
| Operating Temp                   | -20°C - 40°C            |
| SDCM                             | 3                       |
| Energy efficiency class          | D                       |
| Product Weight without Packaging | 1.05 kg                 |

| TECHNICAL INFORMATION          |                     |
|--------------------------------|---------------------|
| Light Source                   | LED                 |
| Colour / Finish                | Grey                |
| IP Rating                      | IP65                |
| Class Protection               | 1                   |
| Internal / External            | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Suspended  |
| Lumen Depreciation             | L80 100,000h        |
| Warranty (Years)               | 5                   |
| CE Mark                        | Yes                 |
| Height                         | 80 mm               |

