












Tornado EVO


Tornado EVO CCT Multi Wattage 1200mm Switch Code: ATORE4/1/DD1

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance









- IP66 non-corrosive batten suitable for industrial applications and ancillary areas
- High efficiency up to 160 Lm/W
- $\bullet \ \ \mathsf{LED} \ \mathsf{performance} \ \mathsf{allows} \ \mathsf{point-to-point} \ \mathsf{replacement} \ \mathsf{of} \ \mathsf{existing} \ \mathsf{fluorescent} \ \mathsf{luminaires}$
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

GENERAL INFORMATION				
Wattage	40W			
Lumens Delivered	3000lm - 6100lm (4000K)			
Lm/W	150lm/W (4000K)			
Beam Angle	120			
CRI	80			
CCT	4000/5000/6500K			
Input	220-240V			
Operating Temp	-20°C - 40°C			
SDCM	3			
Energy efficiency class	D			
Product Weight without Packaging	1.75 kg			

TECHNICAL INFORMATION				
Light Source	LED			
Colour / Finish	Grey			
IP Rating	IP66			
Class Protection	1			
Internal / External	Internal / External			
Surface / Recessed / Suspended	Ceiling, Suspended			
Lumen Depreciation	L80 100,000h			
Warranty (Years)	7			
CE Mark	Yes			
Height	80 mm			