



Tornado EVO

Tornado EVO CCT Multi Wattage 1200mm 1-10V
Code: ATORE4/1/DD4

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance



PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- High efficiency up to 160 Lm/W
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

GENERAL INFORMATION

Wattage	40W
Lumens Delivered	3000lm - 6100lm (4000K)
Lm/W	150lm/W (4000K)
Beam Angle	120
CRI	80
CCT	4000/5000/6500K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	3
Energy efficiency class	D
Product Weight without Packaging	1.75 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Grey
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Lumen Depreciation	L80 100,000h
Warranty (Years)	5
CE Mark	Yes
Height	80 mm

