


Tornado EVO


Tornado EVO Twin 1200mm Switch Dim Self-Test Code: ATOREVO2X4/DD1/SM3





| Category | Battens and Weatherproofs |
|---------------|---|
| Application | Ancillary, Commercial, Education, Healthcare, |
| | Hospitality, Industrial, Retail |
| Specification | Performance |
| | |





· LED Performance allows point-to-point replacement of existing fluorescent luminaires

• High efficiency up to 140 Lm/W

| GENERAL INFORMATION | | | |
|----------------------------------|------------|--|--|
| Wattage | 40W | | |
| Lumens Delivered | 5600lm | | |
| Lm/W | 140lm/W | | |
| Beam Angle | 105/125 | | |
| CRI | 80 | | |
| ССТ | 4000K | | |
| Input | 220-240V | | |
| Operating Temp | 0°C - 40°C | | |
| SDCM | 3 | | |
| Product Weight without Packaging | 1.94 kg | | |

IP65 non-corrosive batten suitable for industrial applications and ancillary areas
Unique luminaire fixing clip design allows option of mounting onto BESA box

· Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

| TECHNICAL INFORMATION | | | |
|--------------------------------|---------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Grey | | |
| IP Rating | IP65 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Ceiling, Suspended | | |
| Lumen Depreciation | L80 54,000h | | |
| Warranty (Years) | 7 | | |
| CE Mark | Yes | | |
| Height | 75 mm | | |

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

