


## Tornado EVO


Tornado EVO Twin 1200mm OCTO Smart Control Code: ATOREVO2X4/OCTO





Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance





· LED Performance allows point-to-point replacement of existing fluorescent luminaires

• High efficiency up to 140 Lm/W

GENER	RAL INFORMATION	
Wattage	40W	
Lumens Delivered	5600lm	
Lm/W	140lm/W	
Beam Angle	105/125	
CRI	80	
ССТ	4000K	
Input	220-240V	
Operating Temp	-10°C - 40°C	
SDCM	3	
Product Weight without Packaging	1.94 kg	

IP65 non-corrosive batten suitable for industrial applications and ancillary areas
Unique luminaire fixing clip design allows option of mounting onto BESA box

· Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Grey		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L80 54,000h		
Warranty (Years)	7		
CE Mark	Yes		
Height	75 mm		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

