

Tornado EVO

Tornado EVO Twin 1500mm 1-10V Self-Test Code: ATOREVO2X5/DD4/SM3





Category	Battens and Weatherproofs	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Retail	
Specification	Performance	





PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- Unique luminaire fixing clip design allows option of mounting onto BESA box
- · Lockable heavy-duty stainless steel clips supplied as standard for added safety and security
- · LED Performance allows point-to-point replacement of existing fluorescent luminaires
- · High efficiency up to 140 Lm/W

GENERAL INFORMATION		
Wattage	60W	
Lumens Delivered	8400lm	
Lm/W	140lm/W	
Beam Angle	105/125	
CRI	80	
CCT	4000K	
Input	220/240V	
Operating Temp	0°C - 40°C	
SDCM	6	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	75 mm	

