












Tornado EVO

Tornado EVO 1200mm Corridor Function Self-Test Code: ATOREVO4/CF/SM3

Category	Battens and Weatherproofs	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Retail	
Specification	Performance	









PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- Unique luminaire fixing clip design allows option of mounting onto BESA box
- $\bullet \ \ \text{Lockable heavy-duty stainless steel clips supplied as standard for added safety and security}$
- LED Performance allows point-to-point replacement of existing fluorescent luminaires
- High efficiency up to 140 Lm/W

GENERAL INFORMATION			
Wattage	20W		
Lumens Delivered	2800lm		
Lm/W	140lm/W		
Beam Angle	105/125		
CRI	80		
CCT	4000K		
Input	220/240V		
Operating Temp	0°C - 40°C		
SDCM	6		
Product Weight without Packaging	1.835 kg		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Grey		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L80 54,000h		
Warranty (Years)	5		
CE Mark	Yes		
Height	75 mm		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750