




Tornado EVO

Tornado EVO 1500mm 1-10V Self-Test Emergency Code: ATOREVO5/DD4/SM3

| Category | Battens and Weatherproofs |
|---------------|---|
| Application | Ancillary, Commercial, Education, Healthcare, |
| | Hospitality, Industrial, Retail |
| Specification | Performance |







PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- Unique luminaire fixing clip design allows option of mounting onto BESA box
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security
- · LED Performance allows point-to-point replacement of existing fluorescent luminaires
- · High efficiency up to 140 Lm/W

| GENERAL INFORMATION | | | |
|----------------------------------|------------|--|--|
| Wattage | 30W | | |
| Lumens Delivered | 4200lm | | |
| Lm/W | 140lm/W | | |
| Beam Angle | 105/125 | | |
| CRI | 80 | | |
| ССТ | 4000K | | |
| Input | 220/240V | | |
| Operating Temp | 0°C - 40°C | | |
| SDCM | 6 | | |
| Product Weight without Packaging | 2.77 kg | | |
| | | | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|---------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | Grey | | |
| IP Rating | IP65 | | |
| Class Protection | 1 | | |
| Internal / External | Internal / External | | |
| Surface / Recessed / Suspended | Ceiling, Suspended | | |
| Lumen Depreciation | L80 54,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Height | 75 mm | | |