









Battens and Weatherproofs

Hospitality, Industrial, Retail

Performance




Tornado EVO

Tornado EVO 1800mm Corridor Function Code: ATOREVO6/CF







Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- IP65 non-corrosive batten suitable for industrial applications and ancillary areas
- Unique luminaire fixing clip design allows option of mounting onto BESA box $\,$
- $\bullet \ \ \text{Lockable heavy-duty stainless steel clips supplied as standard for added safety and security}$
- LED Performance allows point-to-point replacement of existing fluorescent luminaires
- High efficiency up to 140 Lm/W

GENERAL INFORMATION		
Wattage	35W	
Lumens Delivered	5000lm	
Lm/W	140lm/W	
Beam Angle	105/125	
CRI	80	
ССТ	4000K	
Input	220/240V	
Operating Temp	-10°C - 40°C	
SDCM	6	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	80 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750