


# Tornado 110V

Tornado 110V 600mm  
Code: ATORLED2/110V

Category	110V
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

CODE	A	B	C	D
ATORLED0110V	656	360	75	85
ATORLED0410V	1206	960	75	85
ATORLED0610V	1566	960	75	85
ATORLED0810V	1926	960	75	118
ATORLED1010V	2286	960	75	118
ATORLED1210V	2646	960	75	118



- 110V non-corrosive LED batten suitable for all types of 110V site lighting
- Unique luminaire fixing clip design allows option of mounting onto BESA box
- Non-dimmable

- LED Performance allows point-to-point replacement of existing fluorescent luminaires
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security
- Powered by Tridonic

GENERAL INFORMATION	
Wattage	10W
Lumens Delivered	1160lm
Lm/W	120lm/W
Beam Angle	105/125
CRI	80
CCT	4000K
Input	100/240V
Operating Temp	-10°C - 40°C
SDCM	3
Product Weight without Packaging	1.041 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	Yellow
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Lumen Depreciation	L70 54,000h
Warranty (Years)	3
CE Mark	Yes
Height	75 mm

