



Tornado 110V

Tornado 110V 600mm
Code: ATORLED2/110V

Category	110V
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance



Code	A	B	C	D
ATORLED0110V	656	360	75	85
ATORLED0410V	1206	860	75	85
ATORLED0910V	1566	960	75	85
ATORLED022110V	656	360	75	118
ATORLED044110V	1206	860	75	118
ATORLED099110V	1566	960	75	118



PRODUCT FEATURES

- 110V non-corrosive LED batten suitable for all types of 110V site lighting
- Unique luminaire fixing clip design allows option of mounting onto BESA box
- Non-dimmable
- LED Performance allows point-to-point replacement of existing fluorescent luminaires
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security
- Powered by Tridonic

GENERAL INFORMATION

Wattage	10W
Lumens Delivered	1160lm
Lm/W	120lm/W
Beam Angle	105/125
CRI	80
CCT	4000K
Input	100/240V
Operating Temp	-10°C - 40°C
SDCM	5
Product Weight without Packaging	1.041 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Yellow
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Lumen Depreciation	L70 54,000h
Warranty (Years)	3
CE Mark	Yes
Height	75 mm

