



Tornado Pro

Part of the Battens and Weatherproofs product category



Model	Tornado Pro 1200mm XPRESS
Code	ATORP4/1
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	22W
Operating Temp	-20°C - 40°C
Lumens Delivered	4400lm
lm/W	190lm/W
CCT	4000K
Beam Angle	110° (Changeable Optics Available)

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	1.65 kg
Colour / Finish	Clear
Height	83 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9

PRODUCT FEATURES

- Crystal clear polycarbonate base delivers direct and indirect illumination and optical control offers a range of beam angles
- Unique base design supports multiple installation methods, side and end conduit entry locations, adjustable rear mounting clips designed for BESA mounting, and supplied with suspension hooks.
- Compatible with XPRESS emergency and sensors
- Industry leading 190lm/W efficacy
- Available in DALI

ACCESSORIES

AXPL/1/3NM	XPRESS Linear Emergency Kit
AXPL/1/3NM/DA	XPRESS Linear DALI Emergency Kit
AXPL/MWS/1	XPRESS Linear Clip-in Microwave Sensor On/Off
AZH/RP/1	Sensor Remote Programmer





Tornado Pro

IP66

IK10



Part of the Battens and Weatherproofs product category

Model	Tornado Pro 1200mm XPRESS
Code	ATORP4/1
Application	Industrial

