




Tornado PRO


Tornado PRO Twin 1200mm DALI-Emergency Code: ATORPLED2X4/DM3

Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare,
	Hospitality, Industrial, Retail
Specification	Performance









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

 High efficiency up to 161 Lm/W
--

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENEI	RAL INFORMATION	
Wattage	41W	
Lumens Delivered	4500lm	
Lm/W	109lm/W	
Beam Angle	100/120	
CRI	80	
ССТ	4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	
Product Weight without Packaging	2.33 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Height	70 mm	
Accessories	ATORPLED/SSKIT/SINGLE,	
	ATORPLED/SSKIT/TWIN	

