




Tornado PRO


Tornado PRO Twin 1500mm 1-10V Self-Test Code: ATORPLED2X5/DD4/M3

Category	Battens and Weatherproofs		
Application	Ancillary, Commercial, Education, Healthcare,		
	Hospitality, Industrial, Retail		
Specification	Performance		









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	High e	efficiency	up to	161	Lm/W
---	--------	------------	-------	-----	------

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENE	RAL INFORMATION	
Wattage	61W	
Lumens Delivered	6300lm	
Lm/W	103lm/W	
Beam Angle	100/120	
CRI	80	
ССТ	4000K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	
Product Weight without Packaging	2.488 kg	

TECHNICAL INFORMATION					
Light Source	LED				
Colour / Finish	Grey				
IP Rating	IP65				
Class Protection]				
Internal / External	Internal / External				
Surface / Recessed / Suspended	Ceiling, Suspended				
Lumen Depreciation	L80 54,000h				
Warranty (Years)	7				
CE Mark	Yes				
Height	70 mm				
Accessories	ATORPLED/SSKIT/SINGLE,				
	ATORPLED/SSKIT/TWIN				

