



# Tornado PRO

Tornado PRO Twin 1500mm High Output 1 Switch

Code: ATORPLED2X5/HO/1/DD1/M3



Category	Battens and Weatherproofs
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail
Specification	Performance

- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENERAL INFORMATION		TECHNICAL INFORMATION	
Voltage	79W	Light Source	LED
Lumens Delivered	13000lm	Colour / Finish	Grey
Lm/W	161lm/W	IP Rating	IP65
Beam Angle	100/120	Class Protection	1
CRI	80	Internal / External	Internal / External
CCT	4000K	Surface / Recessed / Suspended	Ceiling, Suspended
Input	220-240V	Lumen Depreciation	L80 54,000h
Operating Temp	0°C - 40°C	Warranty (Years)	7
SDCM	3	CE Mark	Yes
UGR	26	Height	70 mm

