




Tornado PRO


Tornado PRO Twin 1500mm High Output 1 Switch Code: ATORPLED2X5/HO/1/DD1

Category	Battens and Weatherproofs	
Application	ication Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Industrial, Retail	
Specification	ecification Performance	









- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary
 areas
- · Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster
 installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs

•	Hiah	efficiency	up t	0 161	Lm/W
	ingn	cincicity	upr	0 101	

- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

GENERAL INFORMATION				
Wattage	79W			
Lumens Delivered	13000lm			
Lm/W	161lm/W			
Beam Angle	100/120			
CRI	80			
ССТ	4000K			
Input	220-240V			
Operating Temp	-10°C - 40°C			
SDCM	3			
UGR	26			
Product Weight without Packaging	1.965 kg			

TECHNICAL INFORMATION				
LED				
Grey				
IP65				
1				
Internal / External				
Ceiling, Suspended				
L80 54,000h				
7				
Yes				
70 mm				

