





# Tornado PRO

Tornado PRO Twin 1500mm High Output 1 1-10V  
**Code: ATORPLED2X5/HO/1/DD4/DM3**

|                      |   |
|----------------------|---|
| <b>Category</b>      | Battens and Weatherproofs   |
| <b>Application</b>   | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail |
| <b>Specification</b> | Performance   |



## PRODUCT FEATURES

- Ultra slim IP65 LED robust non-corrosive batten ideal for industrial applications and ancillary areas
- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- High output 5ft options available

| GENERAL INFORMATION |            |
|---------------------|------------|
| Wattage             | 79W        |
| Lumens Delivered    | 13000lm    |
| Lm/W                | 161lm/W    |
| Beam Angle          | 100/120    |
| CRI                 | 80         |
| CCT                 | 4000K      |
| Input               | 220/240V   |
| Operating Temp      | 0°C - 40°C |
| SDCM                | 3          |
| UGR                 | 26         |

| TECHNICAL INFORMATION          |                     |
|--------------------------------|---------------------|
| Light Source                   | LED                 |
| Colour / Finish                | Grey                |
| IP Rating                      | IP65                |
| Class Protection               | 1                   |
| Internal / External            | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Suspended  |
| Lumen Depreciation             | L80 54,000h         |
| Warranty (Years)               | 7                   |
| CE Mark                        | Yes                 |
| Height                         | 70 mm               |

